

**Safety data sheet**  
**according to UK REACH**

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier** For industrial and professional use only.
- **Trade name:** **MDF Sealer F2071 Clear**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture**  
Surface Coating  
Surface Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**  
HMG PAINTS LIMITED  
Riverside Works,  
Collyhurst Road,  
Collyhurst,  
Manchester,  
M40 7RU  
UNITED KINGDOM  
TEL: +44 (0)161 205 7631  
EMAIL: sales@hmgpaint.com
- **Further information obtainable from:** [www.hmgpaint.com](http://www.hmgpaint.com)
- **1.4 Emergency telephone number:** +44 (0) 161 205 7631 (business hours)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Flam. Liq. 2 H225 Highly flammable liquid and vapour.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** *Danger*
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

**Trade name: MDF Sealer F2071 Clear**

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · 2.3 Other hazards

### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

|                                                                        |                                                                                                                                                                                                         |         |
|------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46-XXXX   | Ethyl Acetate<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319; STOT SE 3, H336                                                                                                                              | 25-50%  |
| CAS: 67-63-0<br>EINECS: 200-661-7<br>Reg.nr.: 01-2119457558-25-XXXX    | propan-2-ol<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319; STOT SE 3, H336                                                                                                                                | 10-25%  |
| CAS: 9004-70-0<br>EC number: 682-719-5                                 | Nitrocellulose (12.3% N)<br>Expl. 1.1, H201                                                                                                                                                             | 10-25%  |
| CAS: 64-17-5<br>EINECS: 200-578-6<br>Reg.nr.: 01-2119457610-43-xxxx    | ethanol<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319                                                                                                                                                     | 10-25%  |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Reg.nr.: 01-2119488216-32-xxxx  | Xylene (mix)<br>Flam. Liq. 3, H226<br>STOT RE 2, H373; Asp. Tox. 1, H304<br>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335<br>Aquatic Chronic 3, H412 | 2.5-10% |
| CAS: 28553-12-0<br>EINECS: 249-079-5<br>Reg.nr.: 01-2119430798-28-xxxx | di-iso nonyl phthalate<br>substance with a Community workplace exposure limit                                                                                                                           | 2.5-10% |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29-XXXX   | Butyl ethanoate<br>Flam. Liq. 3, H226<br>STOT SE 3, H336                                                                                                                                                | ≤ 2.5%  |
| CAS: 67-56-1<br>EINECS: 200-659-6<br>Reg.nr.: 01-2119433307-44-xxxx    | methanol<br>Flam. Liq. 2, H225<br>Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331<br>STOT SE 1, H370                                                                                         | ≤ 2.5%  |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

(Contd. on page 3)

# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

**Trade name: MDF Sealer F2071 Clear**

(Contd. of page 2)

- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Ensure good ventilation/extraction at the workplace.  
Prevent formation of aerosols.  
Hygiene measures:  
Wash hands before breaks and at the end of workday.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed and in a well-ventilated place.  
Keep away from heat.  
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

Trade name: **MDF Sealer F2071 Clear**

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

### 141-78-6 Ethyl Acetate

WEL Short-term value: 400 ppm  
Long-term value: 200 ppm

### 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

### 1330-20-7 Xylene (mix)

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

### 28553-12-0 di-iso nonyl phthalate

WEL Long-term value: 5 mg/m<sup>3</sup>

### 123-86-4 Butyl ethanoate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

### 67-56-1 methanol

WEL Short-term value: 333 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 266 mg/m<sup>3</sup>, 200 ppm  
Sk

- **PNECs**  
CAS No. 1330-20-7 Xylene mixed isomers  
- Fresh water; 0.327 mg/l  
- Marine water; 0.327 mg/l  
- Intermittent release; 0.327 mg/l  
- STP; 6.58 mg/l  
- Sediment (Freshwater); 12.46 mg/kg  
- Sediment (Marinewater); 12.46 mg/kg  
- Soil; 2.31 mg/kg  
CAS No. 123-86-4 Butyl Acetate  
Freshwater: 0.18 mg/l  
Marine water: 0.018 mg/l  
Fresh water sediment: 0.981 mg/kg  
Marine sediment: 0.0981 mg/kg  
Soil: 0.0903 mg/kg  
STP (sewage-treatment plant): 35.6 mg/l  
Intermittent use/release: 0.36 mg/l
- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** When spraying the product, use a respiratory protective device.

(Contd. on page 5)

GB

# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

Trade name: **MDF Sealer F2071 Clear**

(Contd. of page 4)

· **Protection of hands:**

Protective gloves

· **Eye protection:**

Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Liquid

**Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition****Melting point/freezing point:**

Undetermined.

**Initial boiling point and boiling range:** 78 °C· **Flash point:**

-4 °C

· **Flammability**

Highly flammable.

· **Auto-ignition temperature:**

425 °C

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:****Lower:**

2.0 Vol %

**Upper:**

15.0 Vol %

· **Vapour pressure at 20 °C:**

97 hPa

· **Density at 20 °C:**0.944 g/cm<sup>3</sup>· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with water:**

NOT MISCIBLE

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:****Dynamic:**

Not determined.

**Kinematic:**

Not determined.

· **Solvent content:****Organic solvents:**

65.1 %

**Water:**

0.1 %

(Contd. on page 6)

# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

Trade name: **MDF Sealer F2071 Clear**

(Contd. of page 5)

Solids content: 34.8 %

· **9.2 Other information** No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable under normal conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products when stored and handled correctly

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
- Acute Fish toxicity  
n-Butyl acetate  
LC50 18 mg/l  
Species: *Pimephales promelas* (fathead minnow)  
Exposure duration: 96 h
- Chronic Fish toxicity  
n-Butyl acetate  
No data available.
- Acute toxicity for daphnia  
n-Butyl acetate  
EC50 44 mg/l  
Species: *Daphnia* (water flea)  
Exposure duration: 48 h
- Chronic toxicity to daphnia  
n-Butyl acetate

(Contd. on page 7)

# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

**Trade name: MDF Sealer F2071 Clear**

(Contd. of page 6)

NOEC 23 mg/l

Species: *Daphnia magna* (Water flea)

Exposure duration: 21 d

Method: OECD Test Guideline 211

Acute toxicity for algae

n-Butyl acetate

EC50 675 mg/l

Species: *Scenedesmus quadricauda* (Green algae)

Exposure duration: 72 h

Acute bacterial toxicity

EC50 356 mg/l

Species: activated sludge

Exposure duration: 40 h

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1263

- **14.2 UN proper shipping name**

- **ADR**

1263 PAINT (vapour pressure at 50°C not more than 110 kPa)

- **IMDG, IATA**

PAINT

- **14.3 Transport hazard class(es)**

- **ADR, IMDG, IATA**



- **Class**

3 Flammable liquids.

- **Label**

3

(Contd. on page 8)



# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

Trade name: **MDF Sealer F2071 Clear**

(Contd. of page 7)

|                                                                                                                                                         |                                                                                                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                                                                                 | <b>II</b>                                                                                                                                         |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>                                                                                      | <b>No</b>                                                                                                                                         |
| · <b>14.6 Special precautions for user</b><br>· <b>Hazard identification number (Kemler code):</b><br>· <b>EMS Number:</b><br>· <b>Stowage Category</b> | <b>Warning: Flammable liquids.</b><br><b>33</b><br><b>F-E, S-E</b><br><b>B</b>                                                                    |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>                                                                        | <b>Not applicable.</b>                                                                                                                            |
| · <b>Transport/Additional information:</b>                                                                                                              |                                                                                                                                                   |
| · <b>ADR</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>                                                                   | <b>5L</b><br><b>Code: E2</b><br><b>Maximum net quantity per inner packaging: 30 ml</b><br><b>Maximum net quantity per outer packaging: 500 ml</b> |
| · <b>Transport category</b><br>· <b>Tunnel restriction code</b>                                                                                         | <b>2</b><br><b>D/E</b>                                                                                                                            |
| · <b>IMDG</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>                                                                  | <b>5L</b><br><b>Code: E2</b><br><b>Maximum net quantity per inner packaging: 30 ml</b><br><b>Maximum net quantity per outer packaging: 500 ml</b> |
| · <b>UN "Model Regulation":</b>                                                                                                                         | <b>UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II</b>                                                                       |

\*

## SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **MAK (German Maximum Workplace Concentration)**

|            |                             |    |
|------------|-----------------------------|----|
| 64-17-5    | ethanol                     | 5  |
| 14807-96-6 | Hydrated magnesium silicate | 3B |

· **Poisons Act**· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 9)

GB



# Safety data sheet according to UK REACH

Printing date 08.04.2025

Version number: 1.10

Revision: 01.02.2025

**Trade name: MDF Sealer F2071 Clear**

(Contd. of page 8)

· **National regulations:**· **Technical instructions (air):**

| Class | Share in % |
|-------|------------|
| Water | 0.1        |
| I     | 0.4        |
| NK    | 71.0       |

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Full text of H-Statements referred to under sections 2 and 3:**

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department: LABORATORY· **Contact:** Health & Safety Officer· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PNEC: Predicted No-Effect Concentration (UK REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**