

Page 1/9

### Safety data sheet according to 1907/2006/EC, Article 31

Version number: 1.06 Revision: 02.08.2023 Printing date 29.09.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier For Industrial and Professional use only.
- · Trade name: Thinner 2711
- · Article number: AIF682
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture

Surface Coating Surface Coating

- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

HMG PAINTS LIMITED

Riverside Works,

Collyhurst Road,

Collyhurst,

Manchester,

M40 7RU

UNITED KINGDOM

TEL: +44 (0)161 205 7631

EMAIL: sales@hmgpaint.com

- · Further information obtainable from: sales@hmgpaint.com
- · 1.4 Emergency telephone number: +44 (0)161 205 7631 (business hours)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 Suspected of damaging the unborn child. H361d

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light aromatic

*4-hydroxy-4-methylpentan-2-one* 

· Hazard statements

H226 Flammable liquid and vapour.

(Contd. on page 2)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

(Contd. of page 1)

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

*P331* Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· *PBT*: Not applicable. · *vPvB*: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Solvent naphtha (petroleum), light aromatic	50-100%
Reg.nr.: 01-2119455851-35-xxxx	Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H335-H336	
CAS: 123-42-2 EINECS: 204-626-7 Reg.nr.: 01-2119473975-21-xxxx	4-hydroxy-4-methylpentan-2-one  ♦ Repr. 2, H361d; ♦ Eye Irrit. 2, H319; STOT SE 3, H335	10-25%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: Put on breathing apparatus

#### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed and in a well-ventilated place.

Keep away from heat.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

#### 123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm

(Contd. on page 4)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

		(Contd. of )	page 3
· DNELs			
Solvent na	phtha (	(petroleum), light aromatic	
Oral	DNEL	11 mg/day (Con)	
Dermal	DNEL	11 mg/day (Con)	
		25 mg/day (Ind)	
Inhalative	DNEL	$32 \text{ mg/m}^3 (Con)$	
		$150 \text{ mg/m}^3 \text{ (Ind)}$	
123-42-2 4	-hydro:	xy-4-methylpentan-2-one	
Oral	DNEL	3 mg/day (Con)	
Dermal	DNEL	9.4 mg/day (Ind)	
Inhalative	DNEL	$10.4 \text{ mg/m}^3 \text{ (Con)}$	
		66.4 mg/m³ (Ind)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: When spraying the product, use a respiratory protective device.
- · Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Eye protection:



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** 150 °C

· Flash point: 41 °C

(Contd. on page 5)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

	(Contd. of page 4
· Flammability (solid, gas):	Flammable.
· Ignition temperature:	450 °C
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	8.1 Vol %
· Vapour pressure at 20 °C:	5 hPa
Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	NOT MISCIBLE
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	75.0 %
Solids content:	20.0 %
9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Solvent na	Solvent naphtha (petroleum), light aromatic		
Oral	LD50	3,492 mg/kg (rat)	
Dermal	LD50	3,160 mg/kg (Rab)	
Inhalative	LC50/4 h	>6.193 mg/l (rat)	

(Contd. on page 6)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

(Contd. of page 5)

123-42-2 4	123-42-2 4-hydroxy-4-methylpentan-2-one		
Oral	LD50	3,002 mg/kg (rat)	
Dermal	LD50	13,750 mg/kg (Rab)	
Inhalative	LC50/4 h	7.6 mg/l (Rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Acute Fish toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

LC50 9.22 mg/l

Species: Oncorhynchus mykiss (rainbow trout)

Exposure duration: 96 h

Acute toxicity for daphnia

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 6.14 mg/l

Species: Daphnia magna (Water flea)

Exposure duration: 48 h

Acute toxicity for algae

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

ErC50 2.9 mg/l

Species: Pseudokirchneriella subcapitata (green algae)

Exposure duration: 72 h

Acute bacterial toxicity

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

EC50 1 - 10 mg/l

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish

(Contd. on page 7)

Version number: 1.06 Revision: 02.08.2023 Printing date 29.09.2023

Trade name: Thinner 2711

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>

(Contd. on page 8)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

	(Contd. of page
· Stowage Category	A
· 14.7 Transport in bulk according to A	Annex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
-	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL
Ç	HAZARDOUS

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	100.0

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Full text of H-Statements referred to under sections 2 and 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 9)

Printing date 29.09.2023 Version number: 1.06 Revision: 02.08.2023

Trade name: Thinner 2711

(Contd. of page 8)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* \* Data compared to the previous version altered.